


We understand that

EVERY PURCHASE MATTERS



Quality Products. Improving Lives. Protecting the Environment.

Working Out Wonders with



Diamond Plaster™

Undulation to Perfection



About Our Company


Diamond Plaster is a quality product from the trusted house of Diamond Frames Pvt. Ltd. Diamond Frames is a fast paced growing company with universal big ideas. For over 6 years, we have been providing professional service combined with the trusted reliability to our cherished clients. With a range of expertise, we have a strong relationship with renowned stakeholders in the market.

Benefits of Diamond Plaster

- Direct single coat application
- Totally maintenance free
- It is compatible with any type of paint
- Available in 20kg packaging
- Free of shrinkage cracks
- Attractive and smooth finish
- True color shade and gloss for paints with enhanced light reflectance

Technical Drivers of Diamond Plaster

- Approx. Coverage - 80-90 m²/ton*
- Initial Setting Time - 15 - 20 mins
- Final Setting Time - 20 - 25 mins
- Bulk Density (Dry) - 650 - 770 Kg/m³
- Bulk Density (Wet) - 1.4 - 1.5 gm/m³



Diamond Plaster™
Undulation to Perfection

Marketed by:

DIAMOND FRAMES PVT LTD

Regd. Office : #4, Corporation Shopping Complex, Project-II, Brewery Road, Shenoy Nagar, Chennai-30.

Branch Office: Hyderabad | Bangalore | Mumbai

How to Apply Diamond Plaster

- Apply plaster on the background and make it free from dust by brushing with broom. It should also be washed to clean the traces of mould oil.
- More spread and higher coverage is got by wetting the surface prior to application.
- Diamond Plaster is mixed with water using a rod and a paste is made. Plaster should be mixed with water and not to be done the other way.
- To have a right mix the ratio of water to plaster should be: 1 part of water:1.5 Part of plaster.
- Depending upon the requirement prepare the plaster mix.
- Do not add additional dry material once the mix has begun to set, because the performance properties of the plaster will get altered.
- Do not use wet brush on to the finished surface, as that would spoil the surface by leaving permanent brush marks.
- A single coat should not exceed 13mm in thickness, If the required thickness is more than 13mm, additional plaster coats should be applied but a single coat should not exceed 13mm in thickness.
- It would normally take 72 hrs approx. to get dried, based on the thickness and weather conditions. Once dried the surface is ready for painting.

24x7
CUSTOMER CARE
HELPLINE

+91 91 76 76 8000

*Based on the site conditions

url: www.diamondframes.in | email: diamondframes@yahoo.com